


Single Phase  
String Inverter

## X1-Air



**Simple.**  
**Reliable.**  
**Efficient**



High  
Efficiency



Wide Voltage  
Range



Remote  
Monitoring



IP65  
Rated

2.5kW

3kW

3.3kW

### X1-2.5-S / X1-3.0-S / X1-3.3-S

SolaX have developed a range of single phase inverters unrivalled in the industry for their quality, reliability and efficiency. The SolaX single phase inverters boast a wide MPPT voltage range to allow for more energy harvesting and have a maximum input voltage of 580V, with a maximum efficiency of 97.6%. In addition, SolaX single phase inverters are IP65 rated, have no internal fan and come with optional 'plug & play' WIFI.





# X1-AIR (SINGLE PHASE)

**X1-2.5****X1-3.0****X1-3.3****INPUT (DC)**

Max.PV array power [Wp]	2700	3200	3450
Max.DC voltage [V]	600	600	600
Nominal DC operating voltage [V]	360	360	360
Max. input current [A]	10	10	10
Max. short circuit current [A]	12	12	12
MPPT voltage range[V]	70-580	70-580	70-580
Start operating voltage[V]	80	80	80
No. of MPP trackers	1	1	1
Strings per MPP tracker	1	1	1

**OUTPUT AC**

Nominal AC power [VA]	2500	3000	3300
Max. AC power [VA]	2500	3000	3300
Nominal grid voltage(AC voltage range) [V]		220/230/240; 180~280	
Nominal grid frequency/range [Hz]		50/60; ±5	
Nominal AC current [A]	10.8	13.0	14.3
Max. AC current [A]	12	14	15
Displacement power factor		0.8 leading ~ 0.8 lagging	
THDi, rated power [%]		<2	

**EFFICIENCY**

MPPT efficiency [%]	99.9
Euro efficiency [%]	96.8
Max. efficiency [%]	97.1

**POWER CONSUMPTION**

Standby consumption (Night) [W]	<1
---------------------------------	----

**STANDARD**

Over voltage protection	YES
Over current protection	YES
DC isolation impedance monitoring	YES
Ground fault current monitoring	YES
DC injection monitoring	YES
RCD protection	YES
Safety	EN62109-1/-2
EMC	EN61000-6-2;EN61000-6-3;EN61000-3-2;EN61000-3-3
Certification	G98;AS4777;VDE4105; EN50549; CEI0-21

**ENVIRONMENT LIMIT**

Degree of protection(according to IEC60529)	IP65
Operating temperature range [°C]	-25~+60(de-rating at 45)
Max. operation altitude [m]	2000
Humidity [%]	0~100 (condensation)
Storage temperature [°C]	-25~60
Typical noise emission [dB]	<25

**DIMENSION AND WEIGHT**

Dimensions(WxHxD) [mm]	323*402*119
Weight[kg]	10.5
Cooling concept	Natural
Topology	Non-isolated
Communication interfaces	Pocket WiFi(optional)/Pocket LAN(optional)/Pocket GPRS(optional)/Meter(optional)/RS485/DRM/USB-Upgrade
LCD display	Yes
Standard warranty [years]	5-10